

機械尺寸 (Machine Dimensions)



	參數 \ 機種 SPECIFICATIONS			LG-660C (25")	LG720C (28")	LG-800C (31")
А	裁切厚度	Cutting Thickness	mm (inch)	120 (4.72)	120 (4.72)	120 (4.72)
В	裁切寬度	Cutting Width	mm (inch)	660 (25.98)	720 (28.34)	800 (31.49)
С	裁切長度	Cutting Length	mm (inch)	660 (25.98)	720 (28.34)	800 (31.49)
D	前台面高度	Front Table Length	mm (inch)	540 (21.25)	540 (21.25)	540 (21.25)
Е	檯面高度	Table Height	mm (inch)	900 (35.43)	900 (35.43)	900 (35.43)
F	機台總長度	Machine Length	mm (inch)	1720 (67.71)	1780 (70)	1860 (73.22)
G	機台總寬度	Machine Width	mm (inch)	1510 (59.44)	1570 (61.81)	1570 (61.81)
Н	機台總高度	Machine Height	mm (inch)	1470 (57.87)	1470 (57.87)	1470 (57.87)
	電壓	Electrical Supply		照需求 As required	照需求 As required	照需求 As required
	主機馬達	Blade Motor	KW (HP)	1.5 (2)	1.5 (2)	1.5 (2)
	油壓馬達	Clamp Motor	KW (HP)	1.5 (2)	1.5 (2)	1.5 (2)
	推板馬達	Paper Feeding Motor	KW (HP)	0.375 (1/2)	0.75 (1)	0.75 (1)
	送風馬達	Air Table Motor	KW(HP)	0.2 (1/4)	0.2 (1/4)	0.2 (1/4)
	機台總重量	Net Weight	kg (lbs)	1500 (3300)	1600 (3520)	1800 (3960)

★ 產品規格若有變更,恕不另行通知。Technical data subject to change without notice



8.4 inch touch screen

電子式手動微調開關 Electromagnetic hand wheel for fine tuning



- ■機座以高強度鑄造結構組合,機械運轉穩固,裁切準確
- 8.4吋觸控人機介面,記憶可達24,600點,後擋板精準度達0.01mm
- 對於特別尺寸或新制尺寸,可邊切邊記憶電腦,方便於各種紙張的裁切
- 裁切以電磁式離合器煞車驅動運轉,搭配單渦輪、單劈式下刀,裁切輕捷迅速
- ■電子式手動微調開關,輕巧微調整裁切位置
- 工作台面電鍍、送風方便紙堆移動
- ■安全電眼、電器安全防護設備齊全,操作安全,無職業傷害
- 適用裁切材料: 紙張、紙板、薄木片、碳纖維、電路板、塑膠片...等薄片
- Robust Construction ensures decades of service life and dependability.

- Servo-controlled Micro computer with 8.4 inch touch screen displays precision cut dimensions to resolution of 0.01 m/m, and has 24,600 point memory which allows for free size-setting to increase cutting job storage capacity. New cutting position can be added or edited in memory with changing the entire program.
- Cutting knife is driven by worm providing excellent cutting accuracy.
- Specially designed powerful electromagnetic Clutch & Brake avoids unwanted second knife cycle.
- Electromagnetic hand wheel provides fine tuning in manual mode.
- Hydraulic pressure clamp assures quiet cutting.
- Complete safety and protection devices provide security with no danger for the operator.
- Suitable for cutting paper, cardboard, rubber, cork, veneer, leather, plastic, and more.





高精密度滾珠螺桿與高精密強力線性滑動組合而成可 選購升級雙線性滑軌155公分以上機型為標準配備 Ball Bearing Screw & Linear Rail for highest precision Dual linear Rail standard on model 1550 up

Machine frame is constructed of high strength steel and iron castings to provide high stability and cut accuracy.

■ Nickel Chromium table surfaces with programmable air provides easy materials handling.